

THIS DOCUMENT IS THE PROPERTY OF SELECT CONTROLS INCORPORATED AND IS LOANED TO YOU WITH THE EXPRESS CONDITION THAT IT AND THE INFORMATION CONTAINED IN IT ARE NOT TO BE USED, DISCLOSED, OR REPRODUCED IN WHOLE OR IN PART, FOR ANY PURPOSE WITHOUT THE EXPRESS WRITTEN CONSENT OF SELECT CONTROLS INCORPORATED AND THAT NO RIGHT IS GRANTED TO DISSEMINATE OR SO USE ANY INFORMATION CONTAINED IN SAID DOCUMENT.

- NOTES:  
 1. SWITCH TYPE: UNIDIRECTIONAL, SPST, NORMALLY OPEN, NON-LATCHING.  
 2. PHYSICAL CHARACTERISTICS

REF.	CHARACTERISTIC	REQUIREMENTS	TEST METHOD
2.1	WEIGHT	6.0 GRAMS MAX.	SCALE
2.2	SEAL a) HERMETIC b) GROSS	1X10 <sup>-6</sup> SECS HEAVIATM MAX.	MIL-STD-202 TEST METHOD 112 TEST CONDITION C, PRODC. 111A TEST CONDITION D
2.3	TERMINAL STRENGTH	5 LBS. MIN. AXIAL PULL	MIL-STD-202, MTD 211, TEST CONDITION C
2.4	SOLDERABILITY		MIL-STD-202, MTD 208, EXCEPT AGING
2.5	MARKING	*SCIT 3014-1, LOT NO., BLACK EPOXY INK	VISUAL
2.6	LEADS	INSULATED-GOLD PLATED CASE-TIN/LEAD	CERTIFICATION

3. OPERATING CHARACTERISTICS

REF.	CHARACTERISTIC	REQUIREMENTS
3.1	OPEN CONTACTS CONDITION	ON INCREASING ACCELERATION CONTACTS SHALL BE OPEN AT ANY CONSTANT ACCELERATION LESS THAN 1.7G.
3.2	CLOSED CONTACTS CONDITION	CONTACTS SHALL BE CLOSED AT CONSTANT ACCELERATIONS GREATER THAN 2.3g OR MORE, APPLIED IN THE SENSITIVE DIRECTION Z5
3.3	DECREASING ACCELERATION RESPONSE	ON DECREASING ACCELERATION, CONTACTS SHALL BE OPEN AT ANY CONSTANT ACCELERATION LESS THAN 1.5g.
3.4	OPERATING LIFE	1000 OPERATIONS MIN.
3.5	STORAGE LIFE	15 YEARS MIN.

4. ELECTRICAL CHARACTERISTICS

REF.	CHARACTERISTIC	REQUIREMENTS	TEST METHOD
4.1	INSULATION RESISTANCE	30 MEGOHMS MIN. 500 VDC	MIL-STD-202, MTD 302
4.2	DIELECTRIC STRENGTH	500 VAC RMS MAX. 500 VDC 60 HZ, 5 SEC.	MIL-STD-202, MTD 301
4.3	CLOSED CONTACT RESISTANCE	10 OHMS MAX. 0.100 AMP 2.3g MAX.	

3014-1-000  
 D  
 SHT. 2 OF 2

REVISIONS

ALT	DESCRIPTION	BY	CHK	ENG
A	SEE ECN 3014-1-000A	AHN		
B	SEE ECN 3014-1-000B	AHN		
C	SEE ECN 3014-1-000C	AHN		
D	SEE ECN 3014-1-000D	AHN		

5. ENVIRONMENTAL CAPABILITY

REF.	CHARACTERISTIC	TEST METHOD
5.1	OPERATING TEMPERATURE	-65F TO +180F
5.2	VIBRATION (ANY AXIS)	WITH SWITCH MOUNTED HORIZONTALLY, NO CONTACT CLOSURE SHALL OCCUR WITH: 1.) A 0.100 INCH DOUBLE AMPLITUDE FROM 5HZ TO 44.2HZ. 2.) A 10g CONSTANT ACCELERATION FROM 44.3HZ TO 2000HZ.
5.3	SHOCK ACTIVATION	SWITCH CONTACTS CLOSE WHEN SUBJECTED TO SHOCKS IN THE "MUST FIRE" ZONE OF FIGURE 2-1 OF RT04/00-1B3
5.4	CROSS AXIS ACCELERATION	SWITCH CONTACTS CLOSE WHEN OPERATED IN THE 9 SENSITIVE DIRECTION WITH 30g CROSS-AXIS APPLIED SIMULTANEOUSLY WITH 2.3g MINIMUM IN SENSITIVE DIRECTION.
5.5	TEMPERATURE/HUMIDITY	MIL-STD-331, TEST 105.

6. APPLICATION DESIGNED FOR EIT APPLICATION.

MATERIAL		TITLE		PART NO.		DESCRIPTION		REMARKS	
FINISH		ACCELERATION SWITCH		2.0g, N.O.		BILL OF MATERIAL			
NO NOT SCALE DRAWING		SCALE: 2:1		DRAWN: H.A.		CHECKED: H.A.		DATE: 10-9-83	
REMOVE BURRS, BREAK SHARP EDGES		NOTED		APPROVED: [Signature]		APPROVED: [Signature]		SHEET 2 OF 2	
TOLERANCES UNLESS SPECIFIED: ±.005"		DRAWN: H.A.		CHECKED: H.A.		DATE: 10-9-83		REV: D	
MACH. FINISH: ✓		NOTED		APPROVED: [Signature]		APPROVED: [Signature]		SHEET 2 OF 2	

**S** Select Controls Inc.  
 45-3 KNICKERBOCKER AVE.  
 BOHEMIA, N.Y. 11716